



Main

Relay application	Time delay relay
Time delay type	Delays energizing of a load
Range	Acti 9
Product name	IRT
Device short name	IRTA
Signal contacts composition	1 C/O

Complementary

[Ie] rated operational current	8 A AC 250 V 8 A DC 250 V 0.01 A DC 5 V
Impulse duration	> 100 ms
Local signalling	LED green power ON LED flashing time delay
Type of setting	Time delay configuration by rotary knob
Time delay range	0.1...360000 s
Accuracy error	+/- 10 %
Repeat accuracy	+/- 0.5 %
Control circuit voltage	24 V DC 24...240 V AC 50/60 Hz 24...240 V AC 50/60 Hz
[Us] rated supply voltage	24 V DC 24...240 V AC 50/60 Hz 24...240 V AC 50/60 Hz
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	66 mm
Colour	White
Mechanical durability	>= 5000000 cycles
Electrical durability	AC-1 : >= 100000 cycles
Undervoltage behaviour	100 ms
Connections - terminals	Tunnel type terminals 2 cable(s) 1.5 mm ² flexible with cable end Tunnel type terminals 2 cable(s) 1.5 mm ² flexible without cable end Tunnel type terminals 2 cable(s) 2.5 mm ² rigid with cable end Tunnel type terminals 2 cable(s) 2.5 mm ² rigid without cable end

Environment

IP degree of protection	IP40
immunity to microbreaks	<= 20 ms
ambient air temperature for operation	-5...55 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1243 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------